



CRT SS 9900



- Modes: AM/FM/USB/LSB
- Power: AM 30 Watts with modulation, FM 50 Watts, SSB 60 Watts
- Output power adjustable on AM/FM/SSB
- CTCSS and DCS encoder/decoder (included original) 38 CTCSS-104DCS
- Frequency shift (REP function) SPLIT adjustable from 100Hz to 5 MHz
- Steps 100 Hz, 1 KHz, 10 KHz, 100 KHz and 1 MHz
- VFO in frequency mode continued from 28.000 to 29.700 MHz (with step selected)
- -FIN (Fine Tune, RX only / TX only / Both). Adjustable with clarifier, range  $\pm 1.5$  KHz.
- 6 Memories programmable
- Automatic Squelch (AM/FM) ASQ
- Power / Signal Strength / SWR indication
- Numeric indication for SWR value
- Power supply DC displaying
- Dual Watch
- Scan mode
- Roger beep
- Adjustable echo
- Public Address
- Multi-color display (7 colors )
- Backlight key
- Key lock
- Hi Cut (on/off)
- Noise Blanker (on/off)
- Echo (on/off)
- +10 KHz (on/off)
- Roger beep (off, 1-5)
- Microphone Gain (1-36)
- NOG (monitor volume, 1-32)
- TOT (Time Out Timer, Off / adjustable up to 600 seconds)
- TSR (High SWR Protection, On/Off)
- TDC (High Voltage Protection, On/Off)
- SCM (Scan Mode, SQ/Time)
- Programmable by computer (mini USB on back side)
- Reset.
- Size: 157 large x 48 Height x 246 depth
- Weight : 2.1 Kgs

Downloaded from  
[www.cbradio.nl](http://www.cbradio.nl)



CE 0700 !

COMMUNICATION RADIO TÉLÉCOMMUNICATION

PROPRIETAIRE ET IMPORTATEUR POUR L'EUROPE DES MARQUES SUPERSTAR® ET CRT®

Route de Pagny - 21250 SEURRE - France

Tél. International : (33) 3 80 26 91 91 - National : 03 80 26 91 91 - Fax International : (33) 3 80 26 91 00 - National : 03 80 26 91 00

E-mail : [superstar@crfrance.com](mailto:superstar@crfrance.com) - Web.site : [www.crfrance.com](http://www.crfrance.com)

RCS BEAUNE B 352 451 009 - APE 516 JA - TVA : FR77 352 451 009